

Technical Data Sheet

<i>Description:</i>	Natural Natural Oil Care, colorless
<i>Art. No.:</i>	075-000-00010
<i>General Information:</i>	<p>Natural Oil Care, based on natural oils and waxes, dissolved in mild isoparaffines. The maintenance of oiled floors with this Natural Oil Care freshens and impregnates significantly.</p> <p>The use of Natural Oil Care is necessary when the surface is showing scratches or if there are some wear-out effects on the surface. The degree, the frequency and kind of care process is to accommodate to the local conditions and to the demand of the users.</p> <p>The floor should be cleaned from dirt, waxes etc. before using Natural Oil Care.</p> <p>In less used rooms, for example sleeping- or living rooms, it should be enough to use Natural Oil Care 1 to 2 times in year.</p> <p>Middle strong used floors, for example stairs and office rooms, the using frequency should be all 6-8 weeks.</p> <p>Extremely strong floors, for example in shops, restaurants, shopping malls the using frequency should be 8-14 days.</p>
<i>Treatment:</i>	<p>Natural Oil Care is applied sparingly and then spread on the floor with a soft cloth or pad, softly rubbed.</p> <p>Excesses must be absolutely avoided.</p> <p>Important: Natural Oil Care should not be applied with roller or brush tools as this would lead to a higher applied amount and therefore to a longer drying time.</p>
<i>Caution:</i>	Oil-soaked cloth should be stored under water in order to prevent self-inflammation.
<i>Drying:</i>	6 hours after application and polishing progress at room temperature.
<i>Application:</i>	80 – 120 m ² / ltr. depending on the subsurface and its pores.
<i>Dilution:</i>	Natural Oil Care is ready for use.

<i>Cleaning Dilution:</i>	Special thinner, Art. No. 010-000-01354.
<i>Shelf Life:</i>	1 year in an original, unopened canister.
<i>Care:</i>	See special care and maintenance instructions.
<i>Application Restriction:</i>	Because of the complexity of the many different wood types and methods of laying parquet floors, special attention should be given to the technical sealing advisor.
<i>Classification:</i>	Please refer to the technical data sheet.

Klump Coatings manufactures premium quality finishing materials for use in controlled environments utilizing suitable application technologies. It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. The user must always pre-test finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product. Performance data is based upon laboratory testing conducted by Klump Coatings as applied under ideal laboratory conditions. Since substrate, environment and application are all significant factors in actual product performance, this information should serve only as a general guide and customers should conduct appropriate performance testing on production substrate samples to verify suitability to the desired use. (July 2009)