

Technical Data Sheet

Miraphen® UV-Putty for heavy Putty machine

Art. No.: 168

General Information: UV-curing putty for parquet and veneer floors

Qualities: **Miraphen® UV-Putty** is highly viscous, not pumpable with conventional membrane pump and only suitable processing with heavy putty machines.

Preferably the application should follow on (water-based) Miraphen UV- Primer to guarantee a good adhesion and tough elasticity (→ Coin Test) of the whole lacquer structure.

The putty has very high filling properties and excellent grind qualities.

Miraphen® UV-Putty is solvent free and especially environmental friendly.

Treatment: The application is done with a heavy putty machine. Immediately after application, at a belt speed of

12-18 m/min with 1 Hg lamp (80 Watt) can be jellied

or at

12-18 m/min with 2 Hg lamps (80 Watt) can be full cured.

In the second case, we recommend an intermediate sanding (i.e. Grit 280)

As a precautionary measure, we recommend the wearing of rubber gloves and protective glasses.

Applied quantity: ca. 20-50 g/sqm

Viscosity: 20°C. 40 +/- 5 Pas

Shelf life: 6 months in original, unopened canister.

Dangerous Goods Classification:

Please notice our actual Material Safety Data Sheet
Free of heavy metal, formaldehyde and insecticides/pesticides.

Klumpp Coatings manufactures premium quality finishing materials for use in controlled environments utilizing suitable application technologies. It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. The user must always pre-test finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product. Performance data is based upon laboratory testing conducted by Klumpp Coatings as applied under ideal laboratory conditions. Since substrate, environment and application are all significant factors in actual product performance, this information should serve only as a general guide and customers should conduct appropriate performance testing on production substrate samples to verify suitability to the desired use. (July 2009)