



EXTREME MATT

The fourth generation of our UV Top Coat featuring the look and touch of a natural wood floor - @ an unprecedented (micro-) scratch resistance

EASY PROCESSING

- ✚ Can be applied on all common UV lines
- ✚ Top coat @ an application quantity of 4-6 g/m²
- ✚ Highest stability of the viscosity (no running thick in all climate zones)
- ✚ Stable and constant gloss all-over the surface

UNIQUE SELLING POINT

- ✚ Latest top coat technology
- ✚ Gloss level like an oiled surface (up to 3 gloss units @ 60° and @ 85° angle)
- ✚ Highest scratch resistance of the surface against (micro-) scratches (Martindale test)
- ✚ Significantly higher chemical resistance compared to oxidative drying oils
- ✚ Soft and silky touch like natural oil

ADDED VALUE

- ✚ EXTREME MATT provides the look and touch like floors finished with oxidative drying oils, with the durability of a full fledged UV-finish!
- ✚ The most (micro-) scratch resistant extreme matt top coat there ever was!

Comparison of surface properties

	EXTREME MATT	Standard UV-top coat	UV-Oil	Oxi-Oil
Natural appearance	++	-	++	++
(micro-) scratch resistance	++	+	+	-
Chemical resistance	++	++	+	--
Easy-to-clean	++	++	+	-
Variety of colors	++	++	+	+-
Martindale Test DIN EN 16094:2012	MSR-A1/ MSR-B1	MSR-A2/ MSR-B2	MSR-A3/ MSR-B3	Not applicable
Gloss level @ 85°	3-5 units	>8 units	>5 units	>5 units